



REV	DESCRIPTION	DATE
△	RDK-97048	張馨尹 2009/08/21
△	RDK-97127	張馨尹 2009/08/21
△	RDK-98020	張馨尹 2009/08/21
△	RDCM-106052	林淑禎 2017/04/12

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	16	14
AMP.	18	30
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : BLUE
 5. TERMINAL MATERIAL : COPPER
 6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
 7. TERMINAL SURFACE TREATMENT : TIN PLATED
 8. TERMINAL THICKNESS : 0.80 mm

△ Tolerance Unless	
□ otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED(EASY ENTRY) RING TERMINALS			UNIT	mm	
PART NO.	DVR2-4L	MATERIAL	-----	APPROVE		
NUMBER	KA-951272-C	SCALE	SHEET PAGE	CHECKED		
DATE	2007/08/17	4/1	1-4 10F1	DRAWN	謝婉如	