



REV	DESCRIPTION	DATE
△	RDK-98053	洗勝賢 2009/03/17

- NOTE :
1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16
AMP.	3	4	7	10
 2. MAXIMUM ELECTRICAL RATING : 75°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : VINYL
 4. INSULATION COLOR : RED
 5. TERMINAL MATERIAL : BRASS
 6. WIRE RANGE : 22-16 A.W.G. (0.5-1.5 mm²)
 7. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
 8. TERMINAL SURFACE TREATMENT : TIN PLATED
 9. TERMINAL THICKNESS : 0.40 mm

Tolerance Unless Otherwise Specified	
0 > 6 mm ± 0.20	ANGLE
6 > 18 mm ± 0.30	0° > ° REF ±
18 > 30 mm ± 0.40	° > ° ±
30 > 75 mm ± 0.50	° > ° ±

NAME	VINYL-INSULATED DOUBLE CRIMP BULLET DISCONNECTORS				UNIT	APPROVE
PART NO.	VBM1-4	MATERIAL	-----	APPROVE		
NUMBER	KA-95152-C	SCALE	SHEET	PAGE	CHECKED	楊駿孝
DATE	2006/03/27	4/1	1-1	10F2	DRAWN	張馨尹