



REV	DESCRIPTION	DATE
Δ	RDK-97048	張馨尹 2008/06/03
Δ	RDK-97127	謝婉如 2009/04/27
Δ	RDK-98020	謝婉如 2009/04/27
Δ	RDE-102112	謝婉如 2013/10/03
Δ	PPAP-109203	林淑楨 2020/05/04

NOTE:

- MAXIMUM ELECTRIC CURRENT :

A.W.G.	12	10
AMP.	35	50
- MAXIMUM ELECTRICAL RATING : Δ 105°C 600 VOLTS MAX.
- INSULATION MATERIAL : VINYL
- INSULATION COLOR : YELLOW
- TERMINAL MATERIAL : COPPER
- WIRE RANGE : 12-10 A.W.G. (4-6 mm²)
- TERMINAL SURFACE TREATMENT : TIN PLATED
- TERMINAL THICKNESS : 1.00 mm
- Δ 9. () : MEAN REFERENCE.

Δ Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ±
>	mm ± ° ±

NAME	VINYL-INSULATED RING TERMINALS				UNIT	mm	
PART NO.	VR5-10	MATERIAL	-----	APPROVE	張馨尹		
NUMBER	KA-951528-C	SCALE	REV.	SHEET	CHECKED	謝婉如	
DATE	2007/05/03	2/1	1-5	10F1	DRAWN	張馨尹	