



REV	DESCRIPTION	DATE
△	RDK-97048	張馨尹 2008/06/03
△	RDK-97127	謝婉如 2009/04/27
△	RDK-98020	謝婉如 2009/04/27
△	RDE-102112	謝婉如 2013/10/03
△	RDCM-103054	謝婉如 2014/03/18
△	RDCM-105167	林淑楨 2017/06/23

NOTE :

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	12	10	
AMP.	35	50	
2. MAXIMUM ELECTRICAL RATING : △ 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : YELLOW
5. TERMINAL MATERIAL : COPPER
6. WIRE RANGE : 12-10 A.W.G. (4-6 mm²)
7. TERMINAL SURFACE TREATMENT : TIN PLATED
8. TERMINAL THICKNESS : 1.00 mm

△ Tolerance Unless Otherwise Specified	
0 >	mm ± ANGLE
>	mm ± 0° REF ±
>	mm ± ° ° ±
>	mm ± ° ° ±

NAME	VINYL-INSULATED RING TERMINALS				UNIT	mm	⊕
PART NO.	VR5-8	MATERIAL	----	APPROVE	張馨尹		
NUMBER	KA-951527-C	SCALE	SHEET	PAGE	CHECKED	張馨尹	
DATE	2007/05/03	2/1	1-6	10F1	DRAWN	張馨尹	