



REV	DESCRIPTION	DATE
△	RDK-97048	謝婉如 2009/04/13
△	RDK-97127	謝婉如 2009/04/13
△	RDK-98020	謝婉如 2009/04/13
△	PPAP-108676	林淑禎 2019/12/04

NOTE :

- MAXIMUM ELECTRIC CURRENT : 

A.W.G.	22	20	18	16
AMP.	9	12	17	18
- MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
- INSULATION MATERIAL : VINYL
- INSULATION COLOR : RED
- TERMINAL MATERIAL : COPPER
- WIRE RANGE : 22-16 A.W.G. ( 0.5-1.5 mm<sup>2</sup> )
- TERMINAL SURFACE TREATMENT : TIN PLATED
- TERMINAL THICKNESS : 0.75 mm
- $\langle \quad \rangle$  : MEAN REFERENCE.

△	Tolerance Unless Otherwise Specified	
0 >	mm ±	ANGLE
>	mm ±	0° > ° REF ±
>	mm ±	° > ° ±
>	mm ±	° > ° ±

NAME	VINYL-INSULATED RING TERMINALS				UNIT	mm	
PART NO.	VR1-12	MATERIAL	-----	APPROVE	黃宜新		
NUMBER	KA-951081-C	SCALE	REV.	SHEET	CHECKED	黃宜新	
DATE	2006/08/31	3/1	1-4	10F1	DRAWN	張馨尹	